



ADHESIVE TEXTILE

Features:

- 100% polyester, matt surface.
- Combined with UV/Latex/Solvent/Eco-solvent inks.
- Acrylic coating on top surface.
- Perfect for high resolution printing used in POP displays, wall/window graphics, adhesive signage.

Applications:

- POP Display Wall/window graphics Adhesive signage

Details:

Properties	Test method	Metric	Imperial
Base Fabric	DIN 60001	Polyester	
Width Available		0.61/0.914/1.07/1.12/1.27/1.37/1.52	24"/36"/42"/44"/50"/54"/60"
Weight	/	310g/sq.m	9.1 oz/sq.yd
Tear strength	/	14 x 24 N	/
Tensile strength	/	625 x 665 N/5cm	/
Thickness	/	0.32 mm	/
Dimensional stability	/	≤ 0.1mm under 60%°C	/
Temperature resistance	/	-10°C --- 60°C	/
Water resistance	/	yes	/
Humidity resistance	/	N/A	/
Initial Adhesion-Ball Tack	/	>12#	/
Adhesive strenght	/	>48h	/
Service life	/	1 year	/

Ink printability:



NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty