

SpotOn®

EASY BUBBLE FREE APPLICATION

SpotOn® has a unique dot pattern removable adhesive that is virtually undetectable, but allows graphics to be installed with minimal effort, remain in place for the duration of the application, and removed with ease. The film's adhesive allows for easy, bubble-free application of vibrant graphics to a wide range of substrates without the need for tools or wet installation. Available in clear matte, clear gloss, white matte and white gloss finishes. SpotOn® is commonly used for window graphics but can also be used for short-term indoor applications such as wall graphics, tradeshow graphics or retail graphics that require seasonal change out.

- IDEAL FOR INDOOR OR SHORT-TERM OUTDOOR PROMOTIONS
- EASY TOOL & BUBBLE FREE APPLICATION
- CAN BE REMOVED EASILY WITHIN 12 MONTHS

Product Code: **SPOG, SPOM, SPOT, SPOC**

100 Clear or White
micron Monomeric
PVC



(Eco)Solvent
Latex
UV



DOT Pattern
Removable
Adhesive



Widths up to 1370mm



INTERIOR



EXTERIOR

ED QUANTITIE

quaerendum ut. Veri paulo an sea, ei vix propri
ocent mediocritatem, pro ex elitr iudicabit scrip
at his an. Ad ius regione mentitum apeirian, id elig
ni eu. Vim timeam imperdiet temporibus at. Eius

APPLICATIONS

- Indoor Signage
- Retail Promotions
- Window Graphics

Certified for
HP Latex Inks



DRYTAC®

ADHESIVE SCIENCE

www.drytac.com

SpotOn® is a 100µ (4 mil) printable monomeric PVC film with a dot pattern, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single-sided, siliconised clay coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy, bubble-free application of vibrant graphics to a wide range of substrates. SpotOn® is available in clear matte, clear gloss, white matte and white gloss finishes.

- PROP 65 COMPLIANT
- EASY TOOL & BUBBLE FREE APPLICATION
- CAN BE REMOVED EASILY WITHIN 12 MONTHS

INSTALLATION RECOMMENDATION

Please see SpotOn® installation instructions for further details. The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

PRODUCT STRUCTURE

Film	Clear Matte, Clear Gloss, White Matte or White Gloss Monomeric PVC
Adhesive	Dot-Pattern Removable Polyacrylate
Release Liner	140 gsm 1 Side Siliconised PE Coated Kraft

PRODUCT CHARACTERISTIC

Film Thickness	4 mil (100µ)	} 4.5 mil (113µ)
Adhesive Layer	0.5 mil (13µ)	
Film/Adhesive Ratio	4:0.5	
UV Protection Factor	Not Applicable	
Outdoor Durability	Short-Term	
Application Temperature	>41°F (5°C)	
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)	
Fire Rating	B1 (DIN 4102-1) PASS (CAN/ULC-S102)	
Shelf Life	1 year	
Storage Conditions	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity	

DRYTAC®

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013