



Technical data sheet

TOP FLAT White Back

Product name Non-curling White Back Eco White Back

Product code BZF179

Feature
 white/white
 PVC/PET/PVC
 good light stop due to white back
 no curl, perfect product with non-curling at the edge and lay-flat appearance
 Super smooth surface, perfect for high-resolution printing and grey back for good opacity
 Ideal choice for X displays, roll-up displays, window shop advertising, posters, hanging and decorations
 Compatible with Solvent, Eco-solvent, UV inks and screen printing, no lamination required

Application Roll up, X banner, Hanging graphics



Properties	Test method	Metric	Imperial
Average Weight	/	330g/sq.m	9.7oz/sq.yd
Product Structure	/	70micron white surface film+90micron transparent PET+70micron white back film	
Film Thickness	/	0.23mm	/
Available Width Regular Length	/	0.914/1.07/1.27/1.37/1.52/1.60/2.20/2.50/3.20	36"/42"/50"/54"/60"/63"/87"/98"/126"
Composition	/	M 30/50m PVC/PET/PVC	33/55yds

Compatible ink

Eco-solvent	Solvent	UV
-------------	---------	----

Processing instructions

Prior to conversion / further processing, the prints must be allowed to thoroughly dry. We recommend a drying time of 24 hours.
 Roll is recommended to keep sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources.
 Recommended storage temperature and humidity: 15°C [59°F] ~ 35°C [95°F], 20 ~ 65% RH

Additional information

Please store rolls always together with the label / the batch number. Without these, no complaints can be processed.
 Shelf Life 12 months after production date

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty