



Technical data sheet

VERONA FRONTLIT COATED BANNER 510

FEATURES / APPLICATIONS:

- White opaque substrate for high quality frontlit display
- Super strong & durable with softness
- Smooth surface
- Matte & gloss surfaces available
- Excellent for long term outdoor billboard, banners

MATERIAL DETAILS

| PROPERTIES | TEST METHOD | METRIC | IMPERIAL |
|------------------|-------------------|---------------------|--------------------|
| Total Weight | DIN EN ISO 2286-2 | 510g/m ² | 15oz/sq.yd |
| Base Fabric | DIN 60001 | Polyester | Polyester |
| Yarn | DIN EN ISO 2060 | 1100 x 1100 dtex | 1000 x 1000 denier |
| Tensile Strength | DIN EN ISO 1421 | 1700x1320 N/5cm | 191x148 lbs/inch |
| Tear Strength | DIN 53363 | 310x268N | 70x 60lbs |
| Adhesion | DIN 53357 | No delamination | |
| Flame Resistance | DIN 4102 | NFPA 701, B1, M2 | |
| Width | N/A | Max 500cm | 197 inch |

INK PRINTABILITY

| Solvent | Eco Solvent | UV | Latex |
|--------------------------|--------------------------|--------------------------|-------|
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | |
| Screen Printing | Dye Transfer | Dye Direct | |
| <input type="checkbox"/> | | | |
| | | | |

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty